

Raintaina Erosion Pad Filter Cover

The Raintaina Erosion Pad Filter Cover is a self-flushing downpipe erosion pad and filter cover. Downpipes discharge directly onto the permeable cover which effectively prevents detritus, such as leaves, moss and feathers passing forward. The permeable cover is formed from resin bound gravel and removable for easy maintenance.



Raintaina Erosion Pad Filter System provides the following benefits:

- Downpipe discharges directly onto the top of the SEL Raintaina Erosion Pad Filter Cover.
- Self-flushing; removes leaves, moss, feathers and other debris at ground level potentially avoiding overtopping of gutters.
- Provides a treatment phase, which is especially beneficial where planning conditions seek one treatment phase for roof run-off.
- Efficient filtration and silt separation.
- Units situated under each individual downpipe to minimise the risk of system failure.

Inspection / Maintenance

The following routine inspections and maintenance are required:

- Remove litter and surface debris as required.
- 3 Monthly inspection for signs of siltation.
- Every 6 months sweep external surface.
- Every 6 months remove cover and flush both sides with a hose pipe. Cover has a thumb hole to allow easy removal.
- Every 6 months remove the geotextile filter and flush both sides with a hose pipe.
- Records of inspections and maintenance undertaken should be kept by the client

Replacement Filter Covers

For replacement filter covers please contact SEL on 01254 589987 or email sales@selenvironmental.com

Registered Office: Canal House, Bonsall Street, Blackburn, Lancashire, BB2 4DD
Co Reg: 03740358 Vat No: 896 2451 85 Web: www.sel.co.uk Email: info@selenvironmental.com
Managing Director: A Shuttleworth Directors: T Murphy, M Lomax, M Gilsenan, L Warwick